PAN CONNECTORS

Technology from UK

To connect toilets with horizontal and Vertical outlets to standard SWR pipework, Ashirvad has introduced a new range of products that are plumber friendly in nature, made of flexible plastic, the connectors tolerate movement, are leak proof (with multiple fins) and can connect different pipe materials.

APCS2 - Straight - HSN CODE: 39172390

SPIGOT	SWR	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
9.7 - 10.8 cm	9.9 - 10.5 cm	50013426	50	372.00	18600.00

APC02 - 1.8 cm Offset - HSN CODE: 39172390

SPIGOT	SWR 9.9 - 10.5 cm	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
9.7 - 10.8 cm		50013427	45	397.00	17865.00

APC04 - 4.0 cm Offset - HSN CODE: 39172390

	SPIGOT	SWR	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
9.7 - 10.8 cm	9.9 - 10.5 cm	50013428	40	397.00	15880.00	

APCC2 - Collapsible - HSN CODE: 39172390

SPIGOT	SWR 9.9 - 10.5 cm	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
9.7 - 10.8 cm		50013429	25	600.00	15000.00



12.5 x 11.0 cm

The straight connector (APCS2) is used when the spigot outlet on the WC is in line with the SWR pipework system.

WC Inlet rubber bush / Washer

	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
	70003136	400.00	51.00	20400.00

Corrugated Waste Pipe (White) - HSN CODE: 39172390

	Size (cm)	Part No.	Std. Pkg.	MRP Rs Inc. of all Taxes/pc	MRP Rs Inc. of all Taxes/Box
	3.5 cm	70001805	150	86.50	12975.00
	4.2 cm	70001813	100	92.50	9250.00
	4.2 cm (Long)	70001814	80	104.00	8320.00

Specifications for Pan Connectors

- Flexible and made in plastic
- WC load bearing
- · Secure fit on WC side
- Connects different materials
- Multiple fins to ensure water tight fit on SWR side
- Individually packed
- With Lubricant



12.5 x 11.0 cm

The flexible connector (APCC2) is extendable from 22.5 to 55.0 cm and is very useful when the SWR pipework is at a significant distance from the WC spigot outlet or if it is in a vertical position.



12.5 x 11.0 cm 12.5 x 11.0 cm

The two ranges of offset connectors (APCO2 and APCO4) are useful if there is a mismatch between the centres of the spigot on the WC and the SWR pipework. Offsets of up to 4.0 cm can be catered to, by these two WC pan connectors.